

TELESCOPIC TRUCK MOUNTED PLATFORM SPECIFICATION

CTEB-LIFT 200 HY


TECHNICAL DATA

- Telescopic boom
(3 elements: main boom + 2 telescopic extension)
- $\pm 195^\circ$ non continuous turret rotation on bearing turntable
- Fully hydraulic controls with bi-directional levers on the basket
- Fully hydraulic controls at ground level installed on the turret base
- Outreach controlled by an hydraulic limit switch
- Engine Start/Stop control from basket
- Anti slip aluminium deck
- Innovative fully aluminium basket or standard glass filled nylon base with fiberglass frame
- 65° Right + 65° Left hydraulic rotating basket
- Automatic basket levelling by hydraulic parallelogram
- N° 4 hydraulic straight down outriggers (HS type) with ground pressure sensors

AVAILABLE OPTIONS

- Working light in the basket
- 12V or 24V electric system
- 230V AC EC electric socket in the basket

DIMENSIONS



TELESCOPIC TRUCK MOUNTED PLATFORM SPECIFICATION

CTEB-LIFT 200 HY

PERFORMANCE



20 m*



300/250/80 kg



1400x700x1100
mm




8,4/9,2/13,3 m*



18 m

GVW min 5,5 t

WORKING ENVELOPE



* outreach and height max values and repeatability
can change within $\pm 3\%$ due to
manufacturing variation and working condition.

Product specifications are subject to change without notice or obligation. Technical features and drawings in this brochure are for illustrative purposes only. B-LIFT 200 HY - ed. 07/17



CTE S.p.A.
Headquarter

7 Via Caproni - Rovereto (TN) IT, 38068
Ph. +39 0464 48.50.50 - **Fax** +39 0464 48.50.99
info@ctelift.com - **www.ctelift.com**

Factory 5 Loc. Terramatta - Rivoli Veronese (VR) IT, 37010

CTE UK Ltd Enderby Leicestershire - UK

